

ORDER INFORMATION:

SUSBM4 - 051 - $\frac{X}{a} \frac{X}{b} - \frac{X}{c} \frac{X}{d} - \frac{X}{e}$

MATERIAL:

INSULATOR : HIGH TEMPERATURE THERMOPLASTIC WITH G/F,
UL94V-0.

CONTACT : PHOSPHOR BRONZE.

CONTACT FINISH : GOLD ON MATING END, TIN ON
TERMINATION END, WITH ENTIRE
CONTACT NICKEL UNDERPLATED.

SHELL : PHOSPHOR BRONZE, NICKEL PLATED.

SPECIFICATION:

CURRENT RATING : 1AMP.

DIELECTRIC WITHSTANDING VOLTAGE : 100V AC.

INSULATION RESISTANCE : 100MΩ MIN.

CONTACT RESISTANCE : 50mΩ MAX.

OPERATING TEMPERATURE : 0°C ~ +50°C.

a. Plated selection :

1 : Gold 3u"

2 : Gold 15u"

3 : Gold 30u"

b. Shell Plated :

1 : NICKEL

c. Insulator Color :

B : Black


d. Insulator material :

N : NYLON (standard)

e. Pack selection:

T : Tube Pack

R : Reel Pack

GENERAL TOLERANCE	DATE H. D. LI	PART NO SUSBM4-051-XX-XX-X
.X ± 0.25	DESIGN H. D. LI	TITLE MINI USB AB FEMALE REVERSE OFFSET 1.1mm SMD TYPE SPIN
.XX ± 0.15	CHECKED Y. M. LU	
.XXX ± 0.05	APPROVED J. F. KANG	 宏揚精密有限公司 HOJAR PRECISION CO., LTD.
UNIT :mm		

